



MTB HYDRAULIC BREAKERS

MORE POWER, LESS WASTE

MTB hydraulic breakers are easy to use for operators and they are designed for all excavator weight and model varieties. They are designed with a focus on *breaking performance*.

MTB breakers are manufactured for the toughest construction demands rock, concrete, asphalt and marble. As **MTB hydraulic breakers** can be *operated in any position*, they can be used for any application such as oversize boulder breaking in quarrying and mining, overhead breaking in tunnelling, concrete breaking for demolition and specialised underwater projects.

Marble Breakers

MR (Marble) serie breakers outer chassis has a completely special design and are produced with wear-resistant materials. Also our **Marble serie breaker's** side surfaces are made as one single piece and without welding. This way the effects of the forces on the side surfaces of the breaker is lowered.

We produce **9 different models** between 1300-7000 kg for marble quarries and heavy working conditions for the excavators in the range of 25-100 tonnes.



MTB 285 MR

MTB 285 MR breakers which are designed to be used in the **Marble series** is produced as 3155 kg for the excavators in the range of 32-45 tonnes. They are designed to be wear resistant for working in the marble quarries.

TECHNICAL INFORMATION

MTB 285 MR Marble Breakers

| | | |
|-------------------------------|-----|-----------|
| OPERATING WEIGHT | kg | 3175 |
| MINI EXCAVATOR CARRIER WEIGHT | T | 32 - 45 |
| OIL FLOW | LPM | 170 - 270 |
| WORKING PRESSURE | Bar | 140 |
| IMPACT ENERGY | J | 6000 |
| FREQUENCY | bpm | 320 - 350 |
| TOOL DIAMETER | mm | 160 |
| VOLUME | Db | 130 |



Contact:



cekici@hidro-rad.hr



+(385) 21 721 041

