

LIDER

TRAILER



3 AXLE LOWBED SEMI TRAILER

Due to the variable loads in size, type, and weight, this model of trailer is usually used as the main trailer for transportation.

These trailers are usually used to transport industrial machines, construction machinery, and heavy industrial equipment.

From 3 to 6 axles, these trailers also have a hydraulic drive system that is controlled remotely or by truck.

- **Hydraulic steering systems (optional)**
- **Self Steering axle systems (Lider Axles)**
- **Extendable (optional)**
- **Different suspension systems (Mechanical –Air)**
- **Manufacturing with special size and type according to load**
- **Custom design**
- **Manufacturing according to your work and transport**
 - Axles : 3 × 14- 16 Tons
 - Wheels : 245/70 – 17,5 235/75 – 19,5 - 275/70 – 22,5 - 12 R / 22,5
 - Air Suspension : 35-55 Tons
 - Mechanic Suspension : 55-70 Tons
 - Tare Weight $\pm 3\%$: 10800-14.000 Kg
 - External Length : 11.5000 – 15.000 mm
 - Platform Length : 8500 – 11.500 mm
 - Platform Width : 2500 + 600 mm (Width / Side Extensions)
 - Platform Height : 850 mm – 1100 mm
 - Extendable Platform : +3000 mm / + 7000 mm
 - EBS Brake systems
 - ABS Brake systems
 - Single – Double (Foldable) hydraulic ramp systems
 - Colors : Customer Request RAL Codes

Contact:



lider@hidro-rad.hr



+(385) 21 721 041

