

LIDER

TRAILER



BITUMEN TANKER

Bitumen transport tanks or as they are also called hot asphalt transport tanks, these tanks are relied on in road construction . These tankers can be used for transport the without heating systems | bitumen and with heating systems bitumen. Single or Double brulor systems

- **Special chrome plating (optional)**
- **With heating system and electric generator**
- **Manufacture with different sizes and capacities**
- **Manufacture of special requests according to customer requests**
- **Include diesel engine or Electrical engine**
- **100 mm - Woolstone or iso glass coating**
- **28 M³ -40M³ Capacity**
 - Axles : 3 × 12 – 16 Tons 4 × 12 – 16 Tons
 - Wheels : 385/65 R 22,5 (Single) 12 R 22,5 (Double)
 - Air Suspension : 35 - 50 Tons
 - Mechanic Suspension : 40 - 60 Tons
 - Tare Weight ±%3 : 7400 Kg (Steering Trunable Axle Options)
 - Volume : 28 M³ - 40 M³ Capacity
 - External Length : 8000 mm - 12000 mm
 - Total Width : 2500 mm
 - Height : 3000-3300 mm
 - EBS Brake systems
 - ABS Brake systems
 - Colors : Customer Request RAL Codes

Contact:



lider@hidro-rad.hr



+(385) 21 721 041

